



MK-316

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard (29CFR 1910.1200)

Made in the USA: RAMCO SPECIALTY PRODUCTS, INC. ◇ 5956 State Road ◇ Bakersfield, CA 93308-3022
 Ph: (800) 334-7071 ◇ Fax: (714) 375-1225 ◇ E-Mail: lwcsramco@ramcospec.com ◇ Web: www.ramcospec.com

SECTION I – PRODUCT IDENTIFICATION

Product Name: MK-316 (Aerosol)	Proper Shipping Name: CONSUMER COMMODITY
Product Number: 1135	Date Prepared: 02/22/2006
Product Description: Pure Stainless Steel Coating	Prepared By: Paul Williams
Information Phone: (800) 334-7071	24-Hour Emergency Phone: (800) 255-3924

NFPA – HMIS CODES

Health	1	Flammability	4	Corrosive	0	Reactivity	3	Personal Protection	B
--------	---	--------------	---	-----------	---	------------	---	---------------------	---

SECTION II – MATERIAL IDENTIFICATION AND INFORMATION

Description	CAS #	313-Chem	Carcinogen	PEL	TWA/TLV	Wt %
Acetone	67-64-1	NO	NO	1000 ppm	1000 ppm	20-40
Toluol	108-88-3	YES	NO	100 ppm	100 ppm	20-40
Xylene (mix)	1330-20-7	NO	NO	100 ppm	100 ppm	05-10
Ethyl Benzene	100-41-4	NO	NO	100 ppm	100 ppm	01-05
Mineral Spirits	64742-47-8	NO	NO	100 ppm	100 ppm	01-05
Propane	74-98-6	NO	NO	1000 ppm	1000 ppm	10-20
n-Butane	106-97-8	NO	NO	800 ppm	800 ppm	10-20

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

*Boiling Point	~ 47°F	Evaporation Rate (n-Bu-Ac=1.0)	N/A
Vapor Pressure of Can (psig @ 68°F)	6226 mm Hg	*Water Solubility (Wt % @ 25°C)	Negligible
*Vapor Density (Air=1.0)	>1	Solids Content	16.3 %
*Specific Gravity (H2O=1 @ 75°F)	0.77-0.90	Viscosity, Typical (cp)	N/A
VOG (Grams/Liter @ 25°C – EPA Method 24)	N/A	*Appearance	Silver Grey Liquid
% Volatile by Volume	N/A	*Odor	Solvent
Total VOC % (Volatile Organic Compounds)	~58	*pH	N/A

*Data Based on Aerosol Concentrate Only.

SECTION IV – FIRE & EXPLOSION HAZARD DATA

Flash Point (Of Concentrate Only)	-2°F (TCC)
Auto Ignition Temperatures	N/A
Flammability Limits in Air	
Lower Explosive Limit Estimated	N/A
Upper Explosive Limit Estimated	N/A
Extinguishing Media	Foam, CO2, Dry Media
Unusual Fire Fighting Procedures	Exposure to temperatures above 120°F may cause bursting.
Special Fire Fighting Procedures	Wear self-contained breathing apparatus and protective clothing. Cool fire-exposed containers to prevent rupturing.
Flammability (as per USA Flame Projection Test)	Extremely-Flammable Spray



MK-316

Page 2 of 2

SECTION V – HEALTH HAZARD DATA & EMERGENCY FIRST AID PROCEDURES

ENTRY ROUTES	ADVERSE/CHRONIC EFFECTS	FIRST AID PROCEDURES
EYES	May cause slight irritation but does not injure eye tissue.	Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists, get medical attention immediately.
INGESTION	Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.	DO NOT INDUCE VOMITING. Seek medical attention immediately.
INHALATION	Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation can cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.	Remove to fresh air. Seek medical attention immediately. If breathing stops, give artificial respiration.
SKIN	Frequent or prolonged contact may cause irritation.	Wash with soap and water. If irritation persists, seek medical attention.
MEDICAL CONDITIONS TO AVOID	No conditions known.	

SECTION VI – REACTIVITY DATA

STABILITY	Stable – Avoid open flames and exposure to high temperatures.
HAZARDOUS POLYMERIZATION	Will not occur – No conditions known
INCOMPATIBILITY	Avoid contact with strong oxidizing agents.
HAZARDOUS DECOMPOSITION	Carbon Dioxide, Carbon Monoxide.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING & USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED – Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.	
WASTE DISPOSAL	Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.
HANDLING & STORAGE	Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120°F.
NFPA Code 30B Rating	Level 3 Aerosol
OTHER PRECAUTIONS	KEEP OUT OF REACH OF CHILDREN – For Industrial/Institutional Use Only. Read and follow label directions.

SECTION VIII – CONTROL MEASURES

RESPIRATORY PROTECTION	None needed for proper use in accordance with label directions. If ventilation is not adequate to reduce vapors below Threshold Limit Value (TLV) levels, use a NIOSH/MSHA approved air-purifying respirator equipped with an organic vapor cartridge.
VENTILATION	Provide local exhaust to keep TLV of Section II ingredients below acceptable limits.
PROTECTIVE GLOVES	None needed for proper use in accordance with label directions. Use chemical resistant gloves if hand contact will be made.
EYE PROTECTION	None needed unless it is anticipated that a splash or spray back will occur, then wear safety glasses or chemical proof goggles.
OTHER PROTECTIVE CLOTHING/EQUIPMENT	None needed for proper use in accordance with label directions.
WORK HYGIENIC PRACTICES	Employees must practice good personal hygiene; washing exposed areas of skin several times daily and before eating, drinking, smoking, using restroom and at end of work period. Remove contaminated clothing and launder before reuse.

SECTION IX – TRANSPORTATION DATA

PROPER SHIPPING NAME	CONSUMER COMMODITY
DOT ID NUMBER	N/A
DOT HAZARD CLASS	ORM-D

The information and recommendations set forth herein are presented in good faith and believed to be correct and reliable. RAMCO Specialty Products, Inc. makes no representation as to the completeness or accuracy thereof and supplies information upon the condition that the persons receiving same will make their own determination as to its suitability for their purpose prior to use.

N/D = Not Determined

N/E = Not Established

N/A = Not Applicable

< = Less Than

> - Greater Than

MSDS 2006